

coastline industrial coatings, inc.

3401 Fifth Street – Stafford, Texas 77477 (281) 499-0633

AF-304 Acrylic Sealers & Stains

FEATURES

- Seals the surface
- VOC compliant/water-based
- Durable
- Fast Dry
- Protects against water absorption
- Improves aesthetic appearance

COMPOSITION

Acrylic Resin
Pigmentation varies with color.

TYPICAL USES

- Interior and Exterior
- Above Grade
- Brick, Stone
- Stucco, Plaster
- Exposed aggregate concrete walls, panels and columns, both cast-in-place and pre-cast.

PHYSICAL DATA

COLOR: TRANSPARENT AND STAINS

FINISH: GLOSS / SEMI-GLOSS / FLAT

COMPONENTS: SINGLE

SOLIDS CONTENT: VOL. 22%

VOC: 0.32

WEIGHT / GAL: 7.80 LBS.

THEORETICAL COVERAGE: 353 SQ. FT. / GAL (1 MIL)

FLASH POINT: NONE

DRY TIME @ 55% RH & 77° F:

TOUCH – 15 MIN.

HANDLE – 1 HOUR

SHELF LIFE: 1 YEAR MIN. (UNOPENED)

SURFACE PREPARATION

Prior to coating, all surfaces must be clean, dry and free of all contaminants.

APPLICATION DATA

METHOD: BRUSH, ROLL OR SPRAY

MIXING RATIO: N/A

POT LIFE: N/A

APPLICATION PROCEDURE

1. Mix product thoroughly.
2. Thin only if necessary for workability.
3. For airless spray. Adjust pressure as needed.
4. Apply a wet coat in ever parallel passes, overlap 50 percent to avoid holidays, bare areas and pinholes.
5. Recommended D.F.T. is 0.5 – 1 mil.
6. Clean all equipment with warm soapy water after use.

THINNER: NONE REQUIRED

EQUIPMENT CLEANER: WARM SOAPY WATER

SHIPPING DATA

PACKAGING UNITS:

1 gal. unit, 5 gal. unit, 55 gal. unit

LIMITATION OF LIABILITY

COASTLINE's liability on any claim of any kind, including claims based upon COASTLINE's negligence or strict liability, for any loss or damage arising out of, connected with or resulting from the use of the products, shall in no case exceed the purchase price allowable to the products or parts thereof which give rise to the claim. In no event shall COASTLINE be liable for consequential or incidental damages.